



# Clarity Matrix G3 MX55X2

## LCD Video Wall System

The Clarity® Matrix® G3 MX55X2 is a 55" LCD video wall display with an extreme narrow tiled bezel width of 1.8mm that provides a nearly seamless digital canvas, outstanding tiled visual performance, extended operation and requires minimal installation space. Designed for 24x7 operation, the Clarity Matrix G3 MX55X2 features 700 nits brightness, commercial-grade IPS LCD panel, LED backlight technology and Full HD resolution—making it the ideal video wall for high-impact, mission-critical applications.

*Note: Cat6A STP (shield twisted pair) cables and connectors are required.*



SPECIFICATION	DETAIL
<b>Technology</b>	Commercial-grade LCD
<b>Per Panel Dimensions (Including Mount)</b>	47.7 x 26.8 x 3.6in   1212 x 683 x 91mm
<b>Diagonal</b>	55in   1397mm
<b>Native Resolution Panels</b>	1920 x 1080
<b>Aspect Ratio</b>	16:9
<b>Tiled Bezel Width</b>	0.07in   1.8mm
<b>Thermal Expansion Gap Required</b>	0.4 mm   .02 in
<b>Power Consumption (max/display)</b>	215W
<b>Power supply voltage</b>	100-230V AC ± 10%, 50 to 60 Hz
<b>Power Status</b>	Diagnostics LEDs, health monitoring and alerts
<b>Per Panel Weight (Including Mount)</b>	51lb   23.2kg (Landscape) 54lb   24.5kg (Portrait)
<b>Shipping weight</b>	46lbs   48.1kg (single pack) / 157lbs   71.3kg (dual pack)
<b>Mounted Depth</b>	3.6in   91.44mm (wall to front of display)
<b>Brightness (typ)</b>	700 cd/m <sup>2</sup> or nits
<b>Contrast ratio (full field)</b>	1400:1
<b>Contrast Ratio - Dynamic</b>	30000:1 (typ)
<b>Response Time (typ)</b>	8 ms
<b>Full viewing angle</b>	178°
<b>Video Inputs (Controller)</b>	4x HDMI 2.0 (w/ HDCP 2.2), 1x DisplayPort 1.2

<b>Video Outputs (Controller)</b>	9-Output Controller: 9x RJ45 8P8C, 1x DisplayPort 1.2   4-Output Controller: 4x RJ45 8P8C, 1x DisplayPort 1.2
<b>Video Extension built-in</b>	200ft   60m over STP CAT6
<b>Control</b>	IR Remote Control, RS-232, USB, Network, Leyard WallDirector Software
<b>Sync</b>	Mini BNC In/Out
<b>Backlight control</b>	Individual and wall control
<b>Backlight sensing and reporting</b>	At display level
<b>Display module position sensing</b>	Auto-sensing integrated
<b>Backlight life (1/2 brightness)</b>	50,000 Hrs
<b>Power Supply</b>	Offboard   Redundant Optional   Hot Swap
<b>Wall Mount</b>	Planar® EasyAxis™ Mounting System   VESA Mount (optional)
<b>Acoustic Noise</b>	LCD: <30dBA (fanless), VC: 45dBA, RPS: <40dBA @ 25°C (77°F)
<b>Heat Load (max/display)</b>	734 BTU/hr
<b>Operating Temperature/Humidity (degrees F/C, relative humidity)</b>	5° to 40° C / 20-90% RH   41° to 104° F / 20-90% RH
<b>Orientation</b>	Landscape or Portrait
<b>Safety regulations</b>	Complies with EN62368-1, FCC Class A, CISPR22/85, CE, EU RoHS
<b>Cat6 Cables and Connectors</b>	Cat6a STP (shield twisted pair) cables and connectors are required.
<b>Touch Technology</b>	Clarity Matrix MultiTouch (optional)
<b>Protection</b>	Planar® ERO-LCD™ (Extended Ruggedness and Optics™) Technology (optional)
<b>Fiber Video Extension Module Option</b>	1 RU rack mount module drives up to 4 displays
<b>Fiber Video Extension Module Outputs</b>	10G Duplex LC SFP+ single mode transceivers supporting distances up to 10km (32.8kft) (Single mode transceivers supporting 2km (6500ft) included) from video wall. Compatible with multi mode transceivers supporting up to 300m (980ft) from the wall. (multi mode transceivers not provided)

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 11/28/2021*

*© Copyright 2021 Planar Systems, Inc. All rights reserved*